



D300 mm



D200 mm



### THE BENEFITS :

- Made in our workshop
- High-intensity LEDs
- Orientable brackets

### Technical specifications

<b>DIMENSIONS &amp; WEIGHT</b>	<p><b>D200mm</b></p> <ul style="list-style-type: none"> <li>• Height : 310mm without the brackets</li> <li>• Width : 265mm</li> <li>• Thickness : 250mm + 200mm for the visor</li> </ul> <p><b>D300mm</b></p> <ul style="list-style-type: none"> <li>• Height : 500mm without the brackets</li> <li>• Width : 380mm</li> <li>• Thickness : 250mm + 280mm for the visor</li> <li>• Weight : 4kg</li> </ul>
<b>MATERIALS</b>	<ul style="list-style-type: none"> <li>• Black polycarbonate housing, brackets and visors</li> </ul>
<b>POWER</b>	<ul style="list-style-type: none"> <li>• 24V or 230V</li> </ul>
<b>LIGHT SOURCE</b>	<ul style="list-style-type: none"> <li>• High-intensity LEDs : red (cross) and green (arrow)</li> <li>• <b>D200mm</b> : 57 red LEDs and 52 green LEDs</li> <li>• <b>D300mm</b> : 92 red LEDs and 75 green LEDs</li> </ul>
<b>POWER</b>	<ul style="list-style-type: none"> <li>• <b>D200mm</b> : red signal = 4VA / green signal = 5VA</li> <li>• <b>D300mm</b> : red signal = 6VA / green signal = 6VA</li> </ul>
<b>FIXATION</b>	<ul style="list-style-type: none"> <li>• Orientable brackets or straps</li> </ul>
<b>PROTECTION RATING</b>	<ul style="list-style-type: none"> <li>• IP55</li> </ul>
<b>OPTIONS</b>	<ul style="list-style-type: none"> <li>• Contrast sheet metal</li> </ul>